
# **\$** BENETEAU FIRST 24 SE

Standard Configuration & Options Specifications Version 1.2, valid from 1.1. 2022







# **TECHNICAL DATA**

- Hull lenght: 7,29 m / 23'11"
- Beam: 2,50 m / 8' 2"
- Displacement (MLC\*) with standard keel: 1000 kg / 2205 lbs
- Standard keel
- Draft: lifted keel 0,25 m / 9", lowered keel 2,00 m / 0,82 ft, 6' 7"
- Weight: 300 kg / 661 lbs
- Shallow keel
- Draft: lifted keel 0,55 m / 1'9", lowered keel 1,15 m / 3'9"
- Weight: 430 kg / 948 lbs
- Mainsail (laminate): 24,0 m² / 258 ft²
- Jib (laminate): 15,3 m² / 165 ft²
- Gennaker (nylon): 58,0 m² / 624 ft²
- Mast (carbon fibre): 10 m / 32' 10"
- Boom (carbon fibre): 3,50 m / 11' 6"
- Bowsprit (carbon fibre): 2,08 m / 6'10"
- · Hull/deck material: Vacuum infused GRP
- Insubmersibility volume: 1,6 m³ / 57 ft³
- CE design category: C8
- Naval architect: Manuard YD
- · Industrial design: GIGODESIGN
- · Concept and R&D: Seascape
- Air draft: 11,26 m / 36' 11"
- Height on trailer: 3,4 m / 11' 2" w/o mast 2,25 m / 7' 5"
- Length over all on the trailer: 10 m / 32' 10" w/o mast 9,20 m / 30'
  "

## STANDARD CONFIGURATION

# **CONSTRUCTION**

- Hull and deck constructed with vacuum infusion of Vinyl ester resin, Airex PVC foam and Soric GRP sandwich with unidirectional and multiaxial laminates
- The hull is reinforced with infused GRP stringers in the keel and in bow sections
- · The deck comes with high traction non-skid moulded antiskid

- Two transoms hung rudders built of GRP foam sandwich and aluminium casings
- Hull and deck are moulded in single tone off-white RAL 9003
- · The hull is prepared for the application of antifouling
- Underwater areas finished in gelcoat and faired, with possible flaws and imperfections, prepared for sanding and application of epoxy primer and antifouling

## **KEEL ARRANGEMENT**

- Swinging keel build in GRP vinyl ester composite with lead bulb insert
- · Custom made manually operated stainless steel keel winch
- Keel head and edges protected with epoxy primer
- · Slotstrip / keel lips closing the exit of the keel box

## **DECK EQUIPMENT**

- 45 cm / 18-inch high pushpit, pulpit and stanchions with a single lifeline
- Two lifeline cushions
- · Stainless steel bow and stern mooring cleats
- · Stainless steel chain plates for shrouds and forestay
- Coachroof mounted opening hatch 58 x 58 cm / 23 x 23 inches for access to the cabin
- 2x Harken STA20 winches on the coachroof
- 2x Ronstan jib tracks with blocks on the coachroof
- Spinlock clutches for halyards and control lines
- Ronstan blocks and cleats for other controls
- Carbon-look tiller with Ronstan tiller extension
- 2x First branded rope bags from Outils Océans
- · Tempered glass windows on each side of the coachroof
- Spacious storage under the cockpit area with two big hatches
- Bilge pump
- · Attachment point for indoor/outdoor table in the cockpit
- Attachments for engine bracket
- · A numeric lock for the main companionway

## **MAST & RIGGING**

- Compotech high-quality carbon fibre mast and boom with one set of swept-back spreaders, all build in high-quality carbon fibre
- · Carbon parts UV protected
- Continuous 1x19 standing rigging with bottle screw adjusters

- 8:1 outhaul and two reefs
- · Retractable carbon bowsprit controlled from the cockpit
- One tapered mainsheet with mainsheet tackle of ball bearing low
- Friction blocks
- 12:1 boom vang
- · Two jib sheets
- One 2:1 Dyneema main halyard
- One Dyneema jib halyard
- · One Dyneema fractional spinnaker halyard
- Two reef lines
- One bowsprit control line
- One spinnaker tack line
- · Two tapered spinnaker sheets
- One 8:1 cunningham control line
- · Facnor FLT jib furler with the furling line
- Mast transport cover

# STANDARD SAILS

- North Sails mainsail 24 m2/258 ft2, Pentex laminate, triradial cut, with two reefs and bolt rope
- North Sails furling jib 15,3 m2/164 ft2, Pentex laminate, triradial cut with vertical battens and hanks on the luff

# **INTERIOR**

 Bulkheads and furniture lightly covered with a satin finish top paint and white RAL 9003 gel coat on the moulded parts for light, clean and low maintenance finish

### Bow section:

- Double V-berth with insubmersibility volume underneath
- Light and ventilation through big foredeck hatch

#### Central saloon area:

- Bright and spacious main cabin area with large companionway hatch
- Long berths/benches with storage place under the front 1.5 m and insubmersibility volume under the rest
- · Folding covers for the storage area
- Plexiglas companionway washboard and sliding hatch
- EVA foam padding on the floor
- Two Wichard folding pad eyes for lifting straps on the keel-box
- Indoor/outdoor table attachment point on the top of keel-box

# **OPTIONS SPECIFICATIONS**

#### SHALLOW SWING KEEL

- Shallow keel version, with reduced draft lifted position 0,55 m / 1'10", lowered position 1,15 m / 3' 9"
- Increased weight for comparable stability to standard deep keel:
  430 kg / 948 lbs
- Shallow keel in lifted position sticks out of the hull for 0,3 m / 1'; thus, trailer upgrade for shallow keel is required, and the boat can not be beached anymore
- · Operated by standard manual stainless steel keel winch
- GRP vinyl ester composite shell with lead insert
- · Keel head and edges protected with epoxy primer
- Slot strip/keel lips closing the keel slot
- · Possible retrofit from deep to the shallow keel version and vice versa

## CHEMICAL TOILET

- Portable Thetford 335 port-a-potty chemical toilette
- Anticipated storage place in saloon under sliding berth extensions, limited and fixed with the keel-box

## INTERIOR

## COMFORT PACK IN A CHOSEN COLOUR

- Faux leather cushions on the front V-berth and saloon side benches.
- Colour options GREY, TURQUOISE and GREEN
- Wooden sliding berths extensions on both sides of the keel box with cushions in the chosen colour; they extend the bench to a comfortable berth or offer extra seats; when not in use, panels are stored under the entrance and enables free movements in the saloon
- Indoor/outdoor table with storage bag in grey

## FIRST SE CREW BAGS (4 PIECES) IN A CHOSEN COLOUR

- Water repellent PVC easy-to-hang FIRST crew bags
- Attachment points for all two bags in the saloon and two above front V-berth
- FIRST SE handles in red
- · Colour options GREY, WHITE, BLUE, RED or YELLOW
- · Not compatible with Signature comfort packs

#### SAILS

# NORTH SAILS FRACTIONAL GENNAKER IN A CHOSEN COLOUR

- · Fractional soft luff gennaker/asymmetric spinnaker
- Norlon RipStop Nylon 90, 58,00 m2 / 624 sq. ft.
- · Colour options WHITE, RED and BLACK

# NORTH SAILS A5 FURLING GENNAKER & FURLER IN A CHOSEN COLOUR

- · Tight luff fractional A5 furling reacher,
- Facnor FX 1500+ furler set with spliced continuous furling line
- Norlon RipStop Nylon 150, 42,50 m2 / 458 sq. ft.
- · Colour options WHITE, RED and BLACK

### NORTH SAILS J2 HEAVY JIB

- Smaller heavy J2 furling jib for standard jib furler
- Biradial cut, strong laminate material, 12,10 m2 / 130 sq. ft.

# **NAVIGATION & ELECTRONICS**

#### COMPASS PLASTIMO CONTEST 101

- · Compass mounted on bulkhead next to the companionway
- · Compass light connected to navigation lights switch

## **ELECTRIC PACK (12V)**

- Seanapps mobile application and GSM/GPS tracker for live control of your boat (trip logs, anchoring) and real-time alerts (entrance sensor & battery status) with a 1-year subscription
- AGM 12V/70 Ah battery
- Sunbeam Tough series walkable 55W solar on the of the mast with the appropriate regulator
- Interior indirect LED lighting
- Control panel with voltmeter display switches and box under the companionway
- Double USB plug & standard 12V plug
- Masthead tricolour navigation & anchor lights with switches on the control panel

### **B&G TRITON2 INSTRUMENTS PACK**

- B&G Triton2 graphic display installed on the coachroof
- DST810 depth, speed & temperature sensor installed under the front V-berth
- B&G wireless WS320 wind sensor
- · Electrical wiring with a switch on the control panel

## RAYMARINE ST1000 BASIC AUTOPILOT PACK

- Autonomous Raymarine ST1000 tiller pilot
- · Deck and tiller attachment points
- · Electrical wiring with a switch on the control panel

## RAYMARINE EVO100 PERFORMANCE AUTOPILOT PACK

- Raymarine EV100 tiller pilot with EV-1 sensor core
- P70 display mounted on bulkhead next to the companionway
- Raymarine S100 Remote Control
- · Deck attachment points
- · Electrical wiring for the pilot

#### 230V CHARGING PACK

- 230V charger with fuse
- · Shore cable socket in the cockpit
- Shore cable (15 m) with adapter for standard 230V socket
- Internal 230V socket
- Not available in the USA

#### 110V CHARGING PACK

- 110V charger with fuse
- External shore cable socket in the cockpit
- Shore cable (49 ft)
- Internal 110 V socket
- Available only in the USA

## OTHER OPTIONS

#### MOORING PACK

- Spade A60 aluminium anchor (4,5 kg / 10 lbs)
- 40 m/12 mm 131' 3" / 0,47inch rope for the anchor with 10m / 32'10" lead insert

- · Robust Outils Océan storage bag for the anchor and rope
- Mooring lines with spliced ends, 10m/12mm 32' 10"/0,47 inch, 4x
- · Square fenders Outils Océan with fixation ropes, 4x

## **CUSTOM BATHING LADDER**

- · Marine-grade stainless steel bathing ladder
- Robust, made in one single piece (non-foldable), with a handle for easier climbing
- Attached on the stern of the boat, between both rudder blades
- · When not in use, easily stored under the cockpit
- · Compatible with "Stern bench & steering system cover" option

## INDOOR/OUTDOOR TABLE

- · Wooden foldable table, which can be used in the salon or cockpit
- Modular aluminium central leg, powder-coated in white
- Fixation point on the top of the keel box in the salon and on the cockpit floor
- Water repellent PVC storage bag for all the parts in GREY

## STEERING SYSTEM COVER & BENCH ON THE STERN

- The protective cover of the steering system, convenient for clubs and sailing schools
- Comfortable bench on the aft of the cockpit for additional seating and sunbathing area in cruising mode
- Very light option, build in GRP with Honeycomb core and moulded antiskid
- Easily removable equipment secured with pins to reduce weight in racing mode

#### SPINLOCK TILLER EXTENTION

- Spinlock tiller extension EA1200DS, in lieu of standard Ronstan Battlestick
- · Connected to the tiller with rubber joint, which keeps it upright
- Especially recommended option for shorthanded sailing and together with the autopilot options

#### MARINE BEAN BAG

- · Rectangular bean bag for additional comfort on and below the deck
- Spliced fixation rope with plastic snap-shackle
- Colours combinations GREY/WHITE and GREY/BLUE

### REMOVABLE ENGINE BRACKET

- · Removable engine bracket mounted on the stern of the boat
- · For outboards with the long shaft, up to 6 HP

#### CUSTOM COLOUR HULL WRAP

- Hull wrap with folio in custom colour
- If shipped in the container, the "not applied" version should be ordered

## LAZYBAG

- · Lazybag with smart solutions for easier mainsail handling and storage
- Ready-to-roll while under sails, designed to pull lazy jacks to the mast
- Split support battens for easier transport and storage
- Spliced Dyneema lazy jacks with composite shackles attachments
- · Zips along with the bag for the sun tent option

#### SUNSHADE WITH POLES

- Shading option installed over the mainsail and boom
- Tent-poles for extension and fixation of the cover
- Elastics for fixation on the railing
- Tyvek material

## SUN TENT (LAZYBAG ASSEMBLY)

- · Tent shading option for easy installation on the lazy-bag with zipper
- · Elastics for attachment on the railing
- Sunbrella fabric

## **TRANSPORTATION**

# LIFTING STRAPS

- · Three lifting straps connected in one single lifting point,
- Possible craning with stepped mast, as the boat will tilt slightly forward
- · Safety dyneema loop around the mast
- Certified lifting equipment
- Same arrangement, with different lengths of the straps of the shallow keel

## PROVISIONAL MAST CRANE (A-FRAME)

- Simplifying stepping of the mast without a crane
- Lightweight aluminium powder-coated telescopic A-frame providing provisional crane
- Spliced dyneema ropes with hooks for aft fixations
- Dedicated transport and storage bag

# LOK CUSTOMISED TRAILER WITH EQUIPMENT

- · Customised trailer with galvanised steel frame
- · Homologated for max 1600 kg towing weight
- · Single-axis with low profile tires for easier slip launching
- Knott equipment and hand break
- Brakes and dampers for 100km/h admissibility
- · Integrated brake drum washing system
- · Mast support with a manual winch for launching/recovering the boat
- · Aft GRP cradles with EVA foam padding
- Rubber rollers in the middle and pads in the front for easier slip launching
- Front support wheel
- Aft support leg
- Standard European 13-pin connector
- Spare tire
- Trailer straps pack with pads
- Not available in the USA

#### CUSTOM BOAT CRADLES FOR THE TRAILER

 Two GRP cradles with EVA foam padding, supporting boat's stern on the trailer

\*MLC: Mass of the boat in Light Craft Condition includes the weight of the boat in the standard readyto-navigate configuration, keel, standard equipment, sails (mainsail & jib) and engine Beneteau First 24 SE - Seascape edition, Standard Configuration & Options Specifications, Version 1.2, ENG, January 2022 Seascape d.o.o., Podpeč 53, 1352 Preserje , Slovenia. Specifications and descriptions are provided only for your guidance and are subject to change without prior notice. www.beneteau.com www.seascapeedition.com